

# POVZoom - 4K Optical Zoom Camera

Auto-Focus · Hybrid Zoom · Touchscreen Control · NDI®|HX3 & PoE Ready

**Z**owieCAM 4K POVZoom camera crafted in an compact, durable aluminum body. It is the universal 4K Ultra HD POV 18x/25x optical zoom camera with streaming capability plus featuring NDI®|HX3, PoE and distinct tally light. It is rugged, small form-factor, light weight and professional for critical streaming applications. It is cost effective, easy to use, user friendly with top, bottom and side standard tripod mounts. ZowieCAM supports popular USB Type-C charger, PoE 802.3af, WIFI6 and a range of innovative modern features. It is a standalone streaming IP camera with HDMI, SDI UVC output, no PC required.

The POVZoom has three standard 1/4" tripod mounts and gyroscope detection. The design makes it flexible to mount anywhere but always with correct video direction automatically.

The camera features affordable 18x/25x optical zoom Lens, variable aperture and auto focus plus 16x digital zoom capability. It assures the video always crisp, focus sharp with proper video size. That makes it so flexible to fit various applications.

The Sony Ultra-HD 4K back-illuminated and stacked sensor offers crystal clear and rich color accurate video with improved low light sensitivity. It has 4K HDMI, 3G SDI and NDI output simultaneously with embedded audio.

Streaming on-the-go, turn compact ZowieCAM into NDI enabled real-time, low-latency high-quality video over IP workflow. NDI®|HX3 is even better than or equivalent to USB camera. It allows seamless integration of the camera to any NDI environments over a single network cable. It can also work as a webcam and record video to TF or NAS.

The camera can be powered by any handy USB type C power adapter, any DC power adapter via type C to DC adapter or PoE up to 100 meters. Single cable for Video, Audio, Power and Tally in addition to NDI. All above makes it can be easily installed anywhere.

Build-in innovative large touch LCD screen can help to setup the camera quickly and conveniently in the field. You can even watch the camera video and setup the camera by the phone besides HDMI or SDI monitor.

Cut the Cord, Keep the Quality. Stop compromising on wireless video. The POVZoom Camera leverages Wi-Fi 6 with 2T2R MIMO technology to double your data efficiency. This massive boost in throughput allows you to stream high-bitrate NDI®|HX3 signals with the same stability and clarity you'd expect from a wired connection.

The camera has built-in Tally light for multi-camera live production. It supports VISCA over IP or NDI full control from a distance. The Tally can sync to vMix, OBS and Tricaster.

The state-of-art, all-in-one ZowieCAM POVZOOM cameras offer system integrators, streaming professionals, scientific researchers and OEM partners a flexible and affordable solution to stream high quality video over network and video source.



## Highlights :

- ◇ Innovative large touch LCD screen control and setting in the field
- ◇ 18x/25x optical zoom lens with auto focus in POV camera
- ◇ 36x/50x hybrid zoom, and extra 12x digital zoom
- ◇ Sony Ultra-HD 4K back illuminated and stacked 1/2.3" sensor
- ◇ Crisply-detail, low noise 4K video
- ◇ Built-in tally light PVW/PGM in multi-camera productions
- ◇ Accurate auto exposure with zone option
- ◇ Auto, manual, color temp, one push white balance
- ◇ Image freeze support
- ◇ Simultaneous 4K HDMI and 3G SDI outputs with embedded audio
- ◇ Up to 4K30 hardware video encoder
- ◇ H.264 HP/MP/BP or H.265/HEVC MP codec
- ◇ NDI® | HX3 support with better quality and very smallest delay
- ◇ Up to 50mbps bitrate, high bandwidth video stream for best quality
- ◇ NDI® | HX, RTSP, SRT, RTMP(s) streaming up to 4K30
- ◇ NDI or streaming over WIFI
- ◇ Low latency SRT streaming
- ◇ Direct standalone streaming to CDN like YouTube, no PC required
- ◇ Video scale down, Vertical/Portrait and rotation streaming support
- ◇ Simultaneous live out in different RTMP SRT RTSP and multiple CDN
- ◇ Adaptive AAC audio for both embedded audio and analog
- ◇ Analog stereo line in audio input
- ◇ IP VISCA control, NDI® and Web control
- ◇ Simple setup and configuration via login protected web interface
- ◇ Comprehensive control via by PC, smartphone, iPad, Controller and Panel
- ◇ Live video feed to PC, phone and iPad
- ◇ Flexible WYSIWYG OSD, text, logo and stamp image overlay, user-friendly
- ◇ Easy access and plug-and-play installation by mDNS
- ◇ Automatic rotation for vertical/portrait output and encoding
- ◇ Multiple standard tripod mounts also for vertical/portrait video
- ◇ Handy and convenient USB-C, DC, or single cable PoE power
- ◇ RESTFUL API supported for DIY automation and system integrator
- ◇ With two standard 1/4" camera tripod mount
- ◇ OEM/ODM support

# 4K NDI POVZoom Camera

H.265/H.264 4K Encoding · Ultra-Low Latency · Multi-Stream Architecture

## Specification

### Power:

Input : USB TYPE-C, PD 12V, 12W min.  
: 12V DC, 5.5x2.1mm, 12W min  
: PoE(802.3af), CAT5e above

Consumption : <12W Max

### Camera:

Image Sensor : Sony 1/2.3"  
Back-illuminated and stacked Exmor R CMOS  
Effective Pixels : 3840(H) x 2160(V)  
Aperture/IRIS : F1.67-3.67, F1.6-4.3  
Electronic Shutter : AUTO, 1/25(30), 1/50(60), 1/90, 1/100, 1/120, 1/125,  
1/180, 1/250, 1/300, 1/500, 1/600, 1/725, 1/1000,  
1/2000, 1/3000, 1/4000, 1/6000, 1/10000

Lens Zoom Ratio : 18x, 25x  
Hybrid Zoom Ratio : 2x  
Digital Zoom Ratio : 2x Default, 12x Maximum  
Focal Length : f5.5-99mm, f5.3-130mm  
FOV(D/H/V) : 18x, Wide:63.1°/51.9°/39.7°, Tele:3.7°/3.0°/2.2°  
25x, Wide:67.9°/55.0°/41.6°, Tele:2.8°/2.3°/1.7°

Gamma Control : 9 options  
Noise Reduction : 2D/3D, 8 levels  
White Balance : Auto, One Push, R/B Gain, Color Temp, Lock  
Color Temp. : 3000-6500K  
Focus : Auto/Manual/One Push with AF Lock  
Focus Zone : 6 zones and Point Focus  
TOF-assisted focus : Yes  
Exposure : AE/AAE/SAE/M with AE lock  
Mirror/Flip : Automatic/Manual  
Style : 7 options  
Control : English/Chinese IR OSD Menu  
Flicker Cancel : Auto/50/60

### Video:

Video Encoder : H.264 HP/MP/BP, H.265 MP  
Resolution : 4K2160p25/30, 1080p25/30/50/60  
1080i50/60, 720p50/60  
Native Portrait : 1080x1920p25/30/50/60, 720x1280p50/60  
Frame Rate : 24/25/30fps, 50/60fps for 1080/720p  
Codec : H.264/H.265  
Rate Control : CBR/VBR  
Live Preview : Web, HDMI output, SDI  
OSD : English/Chinese, WYSIWYG editor

### Network:

LAN : 100/1000Mbps Gigabit, PoE  
Web : http, https  
WIFI : 802.11a/b/g/n/ac/ax, 2T2R, Dual Band  
Bluetooth : V5.4

### Streaming:

Streaming Out : RTMP(s)/SRT/RTSP  
Bit Rate : Max. 50mbits/s, adjustable  
NDI® : NDI® | HX3/HX2/HX (NDI v5.5, upgradeable)  
Recorder : mp4, mov  
Main Video Stream : Up to 4K  
Secondary Stream : Up to 720p  
Portrait : Vertical streaming

### Video

HDMI Out : 1.4b, YCbCr4:2:2/RGB 4:4:4  
SDI Out : 3G SDI, 800mVpp, 75ohm, 4:2:2(YCbCr)  
NDI : NDI | HX, HX2, HX3  
UVC Out : MJPEG, H.264

### Configuration :

Setting : Smartphone, Tablet, PC, RESTFUL API  
OSD : Text, Logo Caption  
LCD : 3.42", Touch screen  
ZowieX : Windows/macOS, iOS/Android

### Camera Control:

Protocol : VISCA over IP, NDI®, Web, OnVIF  
Local : LCD  
WEB : Browser GUI from desktop or mobile

### Audio :

Sampling : 32, 44.1, 48KHz  
Encoder : AAC, MP3, 16bit  
Bitrate : 32-192kbps  
Audio Input : 0.7VRMS, 20K, 2CH, AGC  
Source : Line In/MIC  
Audio Embedding : HDMI, SDI and NDI

### Tally:

Tally LED : Auto/Manual

### Storage

Network : TF/NAS  
Recorder : mp4, mov, ts

### Software

Firmware : Upgradeable, Linux OS

### Interface:

Power : 1 x USB TYPE C, 1 x RJ 45 PoE  
: 1 x DC 5.5x2.1  
HDMI Output : 1 x TYPE A, Receptacle, 1.4b  
Audio In/Out : 2 x 3.5mm TRS Jack  
Network : 1 x RJ45  
USB : 1 x USB, Type C  
Visible : 1 x LED, Rear  
SDI : 1 x BNC Full size  
Tally : 1 x LED, Front

### Physical

Body size : 122.5L x 76 x 63.2H mm(4.8" x 3.0" x 2.5")  
Weight : 581g (1lb 4.49oz) , Black aluminum  
Operating : 0°C to 40°C(32°F to 104°F), Indoor  
Storage : -20°C to 60°C(-4°F to 140°F)  
Mount : 3 x 1/4"- 20UNC

### Certification

CE, FCC (In progress)

### Ordering

30781-CZZ  
ZZ =25, 25x  
=18, 18x  
C =0  
=1, NDI®|HX3

### Accessories

USB TYPE C 25W PD Charger x 1  
USB TYPE C Cable x1  
Remote Control x1  
Quick Start Guide

\*Accessories is optional and sold separately

\* All specifications are subject to change without notice.

\* Accessories may be different for different product options.

\* Actual object may differ from what shown in catalog.